

# ACCESSORIES

## TOE BOARD PACK

### ML-RJSKAFF-TOE

INTERLOCKING TOE BOARDS TO PROVIDE EDGE PROTECTION. MUST BE USED WHEN PLATFORM HEIGHT IS ABOVE 1.9 METRES.

**PACK CONTAINS:**  
1x 1400 x 600mm TOE BOARD SET



## STABILISER PACK

### ML-RJSKAFFSTAB2

PROVIDES LATERAL SUPPORT WHEN WORKING AT HEIGHTS. MUST BE USED WHEN PLATFORM HEIGHT IS ABOVE 1.9 METRES.

USE 2 STABILISERS TO SUPPORT THE SCAFFOLD WHEN WORKING AGAINST A WALL, AND AN ADDITIONAL 2 TO SUPPORT BOTH SIDES.

**PACK CONTAINS:**  
2 x 2500 x 1500 x 1000mm STABILISERS



## ADJUSTABLE WHEELS

### ML-RJSKAFFWHEEL

HEAVY DUTY 700KG WEIGHT RATED AND LARGER DIAMETER WHEELS, ALLOWING YOU TO STABILISE YOUR SCAFFOLD ON UNEVEN SURFACES. FEATURES A DUAL BRAKE BRACKET AND 350MM THREADED ADJUSTMENT.

**PACK CONTAINS:**  
4 x 150mm (6") ADJUSTABLE SCAFFOLD WHEELS



TO MEET SITESAFE NZ GUIDELINES, TOE BOARDS AND STABILISERS MUST BE USED WHERE THE PLATFORM HEIGHT IS AT 1.9 METRES OR ABOVE.

# FEATURES

AS/NZS1576  
**INDUSTRIAL**  
230KG WORKING LOAD

The Gorilla Mobile Scaffold is a trade tough portable scaffold system. The folding design allows simple and speedy erection and dismantling. The Gorilla Mobile Scaffold is designed to fit through doorways making it the perfect option for indoor use.

With flexibility of the different pack options, the Gorilla Mobile Scaffold meets most indoor and outdoor project needs. Independently tested to AS/NZS1576.1/3, the Gorilla Mobile Scaffold is perfect for the trade and serious DIY user.

## FOLDING DESIGN

FOLDS FOR EASY TRANSPORT AND QUICK SET UP.



## FULL ROUND TUBING

DURABLE AND STRONG ALUMINIUM TUBING WITH A 51MM OUTER DIAMETER AND 2MM WALL THICKNESS.



## QUICK RELEASE LOCKING PINS

STRONG LOCKING PINS FOR QUICK SET UP AND DISMANTLING.



## PLATFORM LOCKING PINS

STABILITY IS ENSURED BY USING AUTOMATIC LOCKING PIN.



## HEIGHT ADJUSTABLE STABILISERS

PROVIDES LATERAL SUPPORT WHEN WORKING AT HEIGHTS. REQUIRED WHEN PLATFORM IS ABOVE 1.9 METRES.



# MOBILE SCAFFOLD



✓ **COMPACT DESIGN**

✓ **LIGHT WEIGHT & PORTABLE**

✓ **MADE TO NZ SAFETY STANDARDS  
AS/NZS1576**



@GORILLALADDERNZ

WWW.GORILLALADDER.CO.NZ



# MOBILE SCAFFOLD

**PLEASE TAKE NOTE\***

ALL MOBILE SCAFFOLD PACKS AND ACCESSORIES ARE SOLD SEPARATELY

## BASE PACK

ML-RJSCAFF-BSE



**PACK CONTAINS:**

- 1x 1329 x 890mm End frame foldings
- 1x 1782 x 680mm Six rung left frame
- 1x 1782 x 680mm Six rung right frame
- 1x 1400 x 600mm Platform with hatch
- 2x 1400mm Horizontal braces
- 4x 127mm (5") Standard wheels

**SAFE PLATFORM HEIGHT UP TO 900mm**

**DIMENSIONS:**

1900H x 1400W x 680Dmm

**MADE UP OF:**

- BASE PACK

**OPTIONAL EXTRAS:**

- ADJUSTABLE WHEELS



**INDUSTRIAL 230KG MAX LOAD**  
MADE TO AS/NZS1576

## RISER PACK

ML-RJSCAFFRISER



**PACK CONTAINS:**

- 2x 1000 x 680mm Guard rails
- 4x 1400mm Horizontal braces

**RISER PACK MUST BE USED IN CONJUNCTION WITH MOBILE BASE PACK**

**SAFE PLATFORM HEIGHT UP TO 1740mm**

**DIMENSIONS:**

2860H x 1400W x 680Dmm

**MADE UP OF:**

- RISER PACK
- BASE PACK

**OPTIONAL EXTRAS:**

- TOE BOARD PACK
- STABILISER PACK
- ADJUSTABLE WHEELS



## TOWER PACK

ML-RJSCAFFTOWER



**PACK CONTAINS:**

- 2x 1782 x 680mm Six rung frames
- 2x 1633mm Diagonal braces
- 1x 1400 x 600mm Platform with hatch

**TOWER PACK MUST BE USED IN CONJUNCTION WITH MOBILE BASE PACK & RISER PACK**

**SAFE PLATFORM HEIGHT UP TO 3440mm**

**DIMENSIONS:**

4555H x 1400W x 680Dmm

**MADE UP OF:**

- RISER PACK
- TOWER PACK
- BASE PACK

**COMPULSORY ACCESSORIES\*:**

- TOE BOARD PACK
  - STABILISER PACK
- OPTIONAL EXTRAS:**
- ADJUSTABLE WHEELS



\*To meet SiteSafe NZ Guidelines, toeboards and stabilisers must be used where the platform height is at 1.9m or above.